

BITUKOTE®

PRODUCT DATA SHEET

BITUKOTE BLACK BITUMEN PAINT FR

Solvent based fiber reinforced - Mastic

SCOPE

BITUKOTE BLACK BITUMEN PAINT FR is a blend of selected bitumen, solvent and fiber, ready for application on concrete, block work and other cementatious surfaces as a permanent water proofing and damp proofing barrier. On steel it provides excellent protection against corrosion.

USES

BITUKOTE BLACK BITUMEN PAINT FR can be used to protect concrete, blinding, footings, block work below floor slab and other concrete in contact with the ground.

CHARACTERISTICS

* Poduct Reference : Comply with BS 3416 Type -1

* Appearance : Black * Solid Content : Min 75% * Touch Dry : 6 hours at 25°C

* Re - coat : 6 to 24 hours at 25°C

* Coverage : 1 litre/m²

* Sag Test : Does not sag upto 1000 micron

* Specific Gravity : 1.02 Approx @ 25°C

* Recommended coating thickness: 400 - 800 microns dry film thickness per coat.

600 - 1000 microns wet film thickness per coat.

STORAGE & HANDLING

Store in cool, dry condition away from fire, heat and sun light.

SURFACE PREPARATION Ensure the surface is clean, dry, free from oil, grease, dust and other contaminants.

APPLICATION METHOD

Ensure adequate ventilation during application and drying.

Mix well and apply by trowel, or scraper. Application must be continuous and ensure full coverage of the surface without voids and pinholes. Apply @ 1 liter/m² Excess thickness could result in very slow drying.

CLEANING

Clean tools with white spirit or thinner.

WARNING

Flammable product! Keep away from children and sources of fire and heat.

PACKING

20 liter and 200 liter metal drum.

GENERAL INFORMATION

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure the product is suitable for the purpose for which he wishes to use it. Technical consultancy is always available for optimum specification and performance.

Manufactured by :-



Gulf Membrane & Coating Industries W.L.L.

Post Box 10266, State of Bahrain

Tel: 770019 • Fax: 774450 • e-mail:baderco@batelco.com.bh • website: www.gmcibahrain.com