

## ROOFBOND PLASTIC ROOF CEMENT

### SCOPE

Roofbond Plastic Roof Cement is a high grade mastic composed of asphalt and fiber. The material is a soft, pliable mastic that gradually hardens to a coating i.e. elastic, durable and resistant to water. Roofbond Plastic Roof Cement has excellent waterproofing and protecting properties in all weathers.

### USES

Roofbond Plastic Roof Cement is pliable and fiber reinforced. It is ideal for most roof repairs and for stopping roof leak around vent pipes, water spouts, light panels, skylights, gutters, chimneys etc. For best result on water resistance use RAINSHIELD roofing membrane over Roofbond. It can also be used for waterproofing below grade concrete structures such as structural or foundation walls and stone work.

### CHARACTERISTICS

* Product Reference	: Conforms to ASTM D 2822 class - 1
* Appearance	: Black
* Specific gravity	: 1.04 Approx. @ 25°C
* Solid Content	: 75 wt. %
* Consistency	: Trowel or scraper
* Touch dry	: 6 hours @ 25°C
* Coverage	: 1 Litre/m <sup>2</sup>
* Recommended min. coating thickness	: 1-2 coats at 1mm wet film thickness
* Shelf life	: 2 years in a closed airtight container, stored in cool place.

### STORAGE & HANDLING

Keep away from direct sun light and open flames. Use protective hand gloves when using. Always ensure adequate ventilation. Close container after each use.

### SURFACE PREPARATION

The surfaces must be clean and dry. Free from oil, grease, rust, scales, loose paint and other contaminants

### APPLICATION METHOD

Apply Roofbond Plastic Roof Cement by trowel or scraper. One gallon covers approximately 14 sq.ft at the rate 1/8" thickness. To install RAINSHIELD roofing membrane use 1Litre/m<sup>2</sup>.

### CLEANING

All equipment can be cleaned with kerosene, white spirit or thinner

### WARNING

Flammable product !	: Keep out of reach of children. Harmful or fatal if swallowed. If swallowed do not induce vomiting call physician.
Eyes	: Flush with plenty of warm water
Skin	: Wash thoroughly with soap and water.

### GENERAL INFORMATION

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure the product is suitable for the purpose for which he wishes to use it. Technical consultancy is always available for optimum specification and performance.

Manufactured by :-



**Gulf Membrane & Coating Industries W.L.L.**

Post Box 10266, Kingdom of Bahrain