

BITUKOTE BITUMEN PRIMER (solvent)

SCOPE	Bitukote Bitumen Primer (solvent) is cold applied highly penetrative primer based on selected grade of asphalt and solvents.
USES	Bitukote Bitumen Primer is generally compatible with all bituminous waterproofing materials as primer, concrete, masonry, metals, roofing felt membranes and wooden surfaces etc.
CHARACTERISTICS	<ul style="list-style-type: none"> ★ Product reference : Conforms to ASTM D 41 ★ Appearance : Black ★ Service Temperature : - 5° to 70°C ★ Flash point : 40°C ★ Drying time : 6 hours to surface dry. ★ Coverage : Concrete : Approx. 5 Sq. Mtr./Ltr. depending upon the porosity of the surface. : Metal : Approx.. 8Sq. Mtr./Ltr.
STORAGE	Long life in air tight closed containers under normal weather conditions.
SURFACE PREPARATION	Ensure the surface is clean, dry, free from oil, grease, dust and other contaminants. Remove laitence by wire brush or sweep blast. Metal surface must be wire brushed or descaled.
APPLICATION METHOD	Bitukote Bitumen Primer can be applied by brush, roller or sprayed directly on the surfaces for application.
CLEANING	Can be cleaned with any suitable petroleum solvent. Skin : Clean with hand cleanser, followed by soap and water
HEALTH & SAFETY	Bitukote Bitumen primer is solvent and inflammable. Use protective clothing, gloves, masks and goggles etc. Do not smoke, avoid naked flames, sparks and provide proper ventilation. Keep away from children. In the event of accidental splashes, flush eyes with fresh water immediately and obtain medical advice.
PACKING	Available in 4 Ltrs, 20 Ltrs and 210 Ltrs drums.
GENERAL INFORMATION	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure the product is suitable for the purpose for which he wishes to use it. The manufactural reserves the right to change the above specifications without notice.

Technical consultancy is always available to ensure optimum specification and performance.

Manufactured by:-



Gulf Membrane & Coating Industries W.L.L.
 Post Box 10266
 Kingdom of Bahrain
 Tel: (00973) 17770019 Fax: (00973) 17774450
 E-Mail: baderco@batelco.com.bh